

SOT23 SILICON PLANAR DUAL SCHOTTKY BARRIER DIODES

BAS70-04
BAS70-05
BAS70-06

ISSUE 3 - JULY 1995



| | | | |
|------------------------|-------------------------|------------------------|---------------------|
| | | | <p>SOT23</p> |
| SERIES PAIR | COMMON CATHODE | COMMON ANODE | |
| Device Type: BAS70-04 | Device Type: BAS70-05 | Device Type: BAS70-06 | |
| Partmarking Detail: 2Z | Partmarking Detail: 2Z5 | Partmarking Detail: 1Z | |

ABSOLUTE MAXIMUM RATINGS.

| PARAMETER | SYMBOL | VALUE | UNIT |
|--|----------------|-------------|-------------|
| Power Dissipation at $T_{amb}=25^{\circ}C$ | P_{tot} | 330 | mW |
| Operating and Storage Temperature Range | $T_j; T_{stg}$ | -55 to +150 | $^{\circ}C$ |

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

| PARAMETER | SYMBOL | MIN. | MAX. | UNIT | CONDITIONS. |
|---------------------------------|----------|------|------|------|--|
| Breakdown Voltage | V_{BR} | 70 | | V | $I_R=10\mu A$ |
| Reverse Leakage Current | I_R | | 200 | nA | $V_R=50V$ |
| Forward Voltage | V_F | | 410 | mV | $I_F=1mA$ |
| Forward Current | I_F | 15 | | mA | $V_F=1V$ |
| Capacitance | C_T | | 2.0 | pF | $f=1MHz, V_R=0$ |
| Effective Minority Lifetime (1) | τ | | 100 | ps | $f=54MHz, I_{pk}=20mA$ (Krakauer Test Method) |

(1) Sample Test

For typical characteristics graphs see ZC2800E datasheet.